

It's a change for the better.

Choosing a VAIL Titan Select roof gives your home a fresh new look that is built to last with virtually no maintenance.

- Stands up to harsh conditions.

 Solid metal construction provides exceptional resistance to extreme temperatures, high winds and heavy snow loads.
- No hassles. No worries.

 VAIL Titan Select is easy to care for.

 No painting or repair is needed to keep it looking like new.
- Locks tightly in place.

 A special interlocking system locks metal panels on all four sides to keep them firmly in place, even in high wind areas.
- High-performance materials.

 VAIL Titan Select is made from durable, high-quality materials that deliver outstanding performance and weatherability.



LAST-TIME® Brand Products

Since 1974

800-826-7813 www.vailmetalshingle.com www.custombiltmetals.com

Manufactured under license of Vail Metal Systems, LLC patents 5,613,337; D415,848; and D423,122



VAIL Titan Select

from Custom-Bilt Metals

VAIL Titan Select shingles provide the timeless style you want and the durability you need.

Heavy-gauge metal construction ensures that they can stand up to what nature dishes out, including extreme temperatures and high winds. A tough, interlocking shingle design means that the shingles will stay put and keep moisture out. In addition, a lifetime warranty from Custom-Bilt Metals means you can enjoy complete peace of mind.

• Interlocking tab system creates

costly structural upgrades.

One look at *VAIL Titan Select* shingles and it's easy to see how beautiful they are going to be on your roof. With its distinctive styling and broad range of colors, *VAIL Titan Select* lets you create just the right look to express your personality.



It's a new face on exterior design.

VAIL Titan Select panels are folded at intervals across the panel to give the appearance of



traditional dimensional shingles. They are installed "shingle fashion," progressing upward and across from right to left to create a seamless, attractive installation.

A broad array of colors means that you can

perfectly coordinate your roof with your home's exterior color scheme.

Patented interlocking system

• Folded seams create classic

interlocking shingle design.

a waterproof channel and aligns panels during installation.

provides exceptional resistance to high winds and snow loads.

locks panels securely in place on all four sides.

• Lightweight panel eliminates

• Patented hem design

moisture penetration.

prevents wind uplift and

• Solid Galvalume construction

It's uncompromising performance.

VAIL Titan Select shingles are made of heavy-gauge, Kynar-coated Galvalume panels. They are ideal for all areas, especially those that experience severe weather. In most areas, the panels can install easily over existing asphalt roof materials. Their interlocking design makes it virtually impossible for moisture to penetrate the roof deck.

Energy Efficient.

www.vailmetalshingle.com

Featuring the TITAN Cool Roof Reflective Paint System.
Our reflective paint features BASF and Kynar 500 reflective pigmentation technology to deliver highly efficient cooling performance.

Find out more.

For more information on VAIL Titan Select or to download Guide Specifications and Architectural Details, please visit www.vailmetalshingle.com. To learn more about Custom-Bilt Metals complete product line, please visit www.custombiltmetals.com.

Product Specifications

Panel length	34-5/8" long
Panel width	12" wide
Exposure area per panel32.5" x 11.25"	
Panels per square	39
Weight per panel	2.7 lbs., 26 gauge
Weight per square1	07 lbs., 26 aquae

Product Material:

VAIL Titan Select:

26-gauge Kynar 500-coated Galvalume, available in a variety of distinctive colors.

Installation Clips:

Two installation clips required per panel, 78 per square. Clips also required for hip or ridge flashings, 2 per 12" piece.

Trim Flashing:

All trim flashing available in 10' lengths. Flat stock also available for contractor fabrication.

Packaging:

Product delivered in 35" x 7.5" x 13" boxes containing 13 panels each; 3 boxes equal one square.

Product Test Results:

Fire Rating	Class A*
Wind Resistance	110 mph**
Hail Resistance	Class 4 per UL® 2218

Product Certifications:

ICBO ES Report No. ER-5318

Dade County approved (Acceptance No. 04-0920.01). The products have passed wind-driven rain testing at the maximum attainable, 110 mph with 8.8" of water introduced.

* Fire rating test per ANSI.UL® 790

** UL® Wind Resistance Rating, UL® Standard 997